



# MED-62V2713M0A

SKU: 233015



1/2,8" HD Dome, Fix, Day&Night 1920x1080, Lens 2,7-13,5mm, IR LED, 12VDC, IP66

## Main Features

- .....
- 1/2.8" 2.3 Megapixel progressive scan CMOS sensor
- .....
- Compact metal housing for outdoor use
- .....
- Resolution max. 1920x1080 (Full HD)
- .....
- Multisignal: HD-TVI, AHD, CVI, Composite selectable
- .....
- Variofocal 2.8~12mm day&night lens
- .....
- LSC (Lens shading compensation)
- .....

- .....
- Removable infrared cut filter
- .....
- RS-485 control in-output
- .....
- 3D-DNR noise reduction
- .....
- Integral motion detection
- .....
- Scratch resistant hard coated bubble
- .....
- Easy installation, 3-Axis gimbal
- .....

## Specifications

Dimensions (HxWxD)	108x144,4mm
Series	eneo KX-Series
Resolution Pixels	1920x1080
Resolution Pixels	960x576
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Day&Night Switch	ICR
Sensitivity	0,3 Lux
Sensitivity 2	40IRE, at F1.3

# MED-62V2713M0A

Continuation of the specifications

Low Speed Shutter	yes
Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR
Motion Detector	yes
Lens Type 2	Varifocal
Focal Length	2,7 - 13,5 mm
Iris Control	DC
Zoom Factor	4x
Digital Zoom	no
Horizontal Angle of View	95 - 27°
Vertical Angle of View	49 - 15°
Illumination	infrared
Housing	Outdoor
Color (housing)	Pantone Cool Gray 1C
Color (bubble)	clear
Housing material	Aluminium
Heater	no
Blower	no
Video outputs	AHD, composite (CVBS), CVI, HD-TVI
Alarm inputs	no
Alarm outputs	no
Serial interfaces	Coaxitron (HD Protocol)
Analysis functions	Defog
Mounting_4	Ceiling mount, Wall mount
Supply voltage	12VDC
Power consumption	6W
Vandal proof	yes
Operating temperature	-20°C ~ +50°C
Certifications	IK10
Protection rating	IP66
Signal format	AHD @ 2MP, Composite (FBAS), CVI @ 2MP, HD-TVI @ 2MP
Camera built	Dome
Frame Rate	25/30fps @ 1920x1080p
Aperture range (F)	F1,3
Illumination range	approx. 30m
Weight	1.0kg
Manufacturer order number	233015

## Optional Accessory

# MED-62V2713M0A

SKU	Name	Description
-----	------	-------------

# MED-62V2713M0A

Continuation of accessory

230864	AK-11	Camera junction box for wall and ceiling mounting
215644	DOME-WB3	Wall bracket for eneo Dome Cameras MED-62xxxxM0A and IED-62xxxxM0A
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive

## Optional Services

SKU	Name	Description
229233	CON-KAM-AKON	Preconfiguration 1x analog camera Function test, FW update
211125	CUS-SL-F	Extra charge for special paint fixed dome in RAL color
214441	CUS-SL-GK	Painting basic costs once per RAL color and delivery lot

## Your contact person

SLD Security & Communications Ltd.  
 101 Eden Grove Road  
 KT14 7PX Byfleet Surrey  
 GB  
 Tel: +44.7973112104  
 E-Mail: [enquiries@sld.uk](mailto:enquiries@sld.uk)  
 Web: [www.sld.uk](http://www.sld.uk)



SLD Security & Communications  
 Secure by Design